

# Technical Release Notes enaio® Version 9.0

Last updated: 28.01.2019

All software products and all related programs and functions are registered and/or used trademarks of OPTIMAL SYSTEMS GmbH, Berlin or one of its companies. They may only be used with a valid license agreement. The software and its associated documentation are protected by German and international copyright law. Unauthorized duplication and sales is plagiarism and subject to criminal prosecution. All rights reserved, including reproduction, transmission, translation, and storage with/on all kinds of media. For all preconfigured test scenarios or demo presentations: all company and person names which occur in examples or screenshots are fictional. Any resemblance to existing companies or persons is purely coincidental and unintentional.

Copyright 1992 – 2019 by      OPTIMAL SYSTEMS GmbH  
Cicerostraße 26  
D-10709 Berlin

28.01.2019  
Version 9.0

# Contents

Contents .....	3
Technical Release Notes 9.0 .....	5
New Features in enaio® 9.0 .....	6
Update Notes .....	6
Versions.....	6
SETUP .....	6
MSI Packages .....	6
Internal Names .....	7
Full text.....	8
Elasticsearch 6.x.....	8
Installation Elasticsearch 6.x.....	8
Migration Tool.....	8
Update to enaio® 9.0.....	9
Update from enaio® 8.0 to enaio® 9.0.....	10
64-bit Server/Beta .....	10
Installation .....	10
Update to a 64-Bit Server.....	11
Archiving with 64-Bit Servers.....	12
E-mail Management .....	13
'E-Mail' Document Type.....	13
Service 'mailstorage' .....	13
E-Mail Inbox.....	15
E-Mail Viewer .....	15
Administrative E-Mails .....	15
enaio® exchange.....	15
Administration.....	17
New System Roles.....	17
Clauses with Folder Reference .....	17
Rights Group Control.....	18
Clauses for Access Rights .....	18
Workflow: Permitted Object Types.....	19
Info Area of the Record .....	19
Configuration of the Participant Name .....	19
Content Preview .....	20
Add-Ons.....	20
Tables.....	20
W-Templates.....	20
W-Template Selection via Event Script.....	20
System Check.....	21

Authentication with Kerberos.....	22
enaio® client – Cache Directory.....	22
Print out Data of the Security System .....	22
XML Transformation .....	22
COM – GetObjectPattern .....	22
Server-API - GetResultList/GetObjectDetails .....	23
enaio® client.....	23
Color Scheme.....	23
File Format Icon .....	23
Icons for Add-Ons and Buttons.....	24
Substitutions .....	24
Document Sharing.....	24
Hit List Sorting .....	24
Pin Column.....	24
Location Focus.....	24
Register Hit Lists.....	24
The Workflow Inboxes.....	25
Filing tray .....	25
Expression .....	25
Paper Format for Scanning.....	25
enaio® webclient .....	25
enaio® webclient.....	25
Masks in enaio® webclient .....	25
enaio® webclient as a Desktop Application .....	26
enaio® mobile .....	26

# Technical Release Notes 9.0

This document contains information about new developments since the release of version 8.50.

Information about the status of support calls can be obtained from OPTIMAL SYSTEMS, Berlin, department of professional services by e-mail: [support@optimal-systems.de](mailto:support@optimal-systems.de) or via the attached support call/bugfix list.

Please also note all the relevant Technical Release Notes and system requirements from the version you are updating to the current version.

# New Features in enaio® 9.0

## Update Notes

### Versions

Updating enaio® requires some additional steps to update the full-text component, which will be done prior to the update, which will run at 8.50/8.10.

Components, especially microservices that were not part of enaio® in versions 8.0 and 8.10, are not installed by an update and must be reinstalled.

Please also note the Technical Release Notes and system requirements for all intermediate versions.

### SETUP

As usual, all components must be updated by setup or MSI simultaneously – server, clients, and services.

If some components have not been updated, not only functional errors but also security-related errors may occur when accessing data.

### MSI Packages

The client installation via MSI only installs enaio® client and no longer any additional components. So far, optional add-ins and printers could be installed as well. This also applies to updates.

The following components are available as MSI packages:

- enaio Office NG add-in  
enaio\_office\_addin.msi
- enaio Outlook NG add-in  
enaio\_outlook\_addin\_ng.msi
- enaio® search  
enaio\_Search.msi
- enaio® Outlook Add-In (deprecated)

enaio\_outlook\_addin\_deprecated.msi

- enaio® GroupWise Add-On NG

enaio\_groupwise\_addon\_ng.msi

The enaio® office-utilities can still be installed and updated via the setup.

The printer drivers can be installed and updated via the setup or an installation program as before. In addition, an MSI package is also available for the printers.

## Internal Names

Detail preview, content preview, and enaio® webclient require internal names for all object types and fields. When updating a version prior to 8.50, the internal names, if not yet assigned, are initialized by the system. In order for the internal names to become known everywhere, enaio® editor must be used to change and save the object definition and reload the engines. For example, move a dialog element minimally or change the size of an element minimally.

# Full text

## Elasticsearch 6.x

With enaio® version 9.0, Elasticsearch is integrated in the version 6.x instead of 2.x.

There are no differences when reinstalling. Updates require a migration.

For Elasticsearch 6.x, a new full-text index must be created. The full-text index is created before the update while the enaio® 8.50/8.10 is running in order not to disturb the ongoing operation. To do this, Elasticsearch 6.x will be installed on a separate computer with its own full-text index. A migration tool then creates the new index from the existing index.

Thereafter, the update will be carried out by enaio® including the microservices and Elasticsearch 6.x will be integrated with a new index in enaio® 9.0.

Elasticsearch 6.x and the new full-text index can then be moved from the own computer into the existing infrastructure with appropriate adaptation of configuration files.

### Installation Elasticsearch 6.x

Elasticsearch 6.x must be installed for migration on a separate computer. Enough space must be available for the extensive full-text index. This should be on a logical drive with high performance and fast access. Elasticsearch recommends an [SSD hard drive](#).

During installation, the installation directory and the port are specified.

The service requires an administrative account.

The setup is in the following directory:

```
\Win32\Disk1\Microservices\Elasticsearch-6.2.4\
```

After installation and integration into enaio®, enaio® services-admin can access the details pages of the services 'index' and 'search' on the Elasticsearch installation.

### Migration Tool

The migration tool is located in an archive in the following directory:

```
\Win32\Disk1\Microservices\prepareFulltextIndexUpdate\
```

It is unpacked on the installation computer of Elasticsearch 6.x and contains the following files:

- application-prod.yml



Configuration file in which IP and port of Elasticsearch 2.x must be entered.

- `migration-9.0.0.jar`

Executable JAVA file that is started from the batch file.

- `prepareFulltextIndexUpdate.bat`

Batch file into which the path to the JDK 1.8 of Elasticsearch 6.x must be entered before starting.

For example: `D:\Elasticsearch6\jdk\bin\java`

Before starting the migration tool from the batch file, access from this IP to Elasticsearch 2.x must be allowed:

- 8.50: Via the configuration file `elasticsearch.yml` from the directory `\config\` of Elasticsearch 2.x, add the IP of the migration tool to the parameter `intrafind.security.subnet` and restart the service.
- 8.10: Via the configuration file `osfts.properties` from the directory `\configuration\` of Elasticsearch 2.x, add the IP of the migration tool to the parameter `security.allowedhosts` and restart the enaio® full-text service.

Then the Elasticsearch 6.x service can be started and the batch file can be executed.

The migration logs into the subdirectory `\log\`.

The process of the migration can be viewed via the following URL:

`http://[ES6-host]:[ES6-port]/systeminfo/_search`

The migration tool should be started several times. This migrates the data that has been newly created in the meantime in enaio® 8.50/8.10.

## Update to enaio® 9.0

This is followed by the update to enaio® 9.0 with all components.

After the update, Elasticsearch 2.x will continue to be integrated with the old full-text index via the 'index' and 'search' microservices.

Before launching the microservices, the configuration file `application-es.yml` is used to enter the IP and port of Elasticsearch 6.x.

If Elasticsearch and Microservices are not running on the same computer, the IP address of the microservice must also be entered into the configuration file `intrafind.yml` from the directory `\config\` as `security.subnet`.

Then Elasticsearch 6.x will be available with the new index database.

To upgrade from enaio® 8.10 to enaio® 9.0, enaio® index-manager must then be installed and run.

Details can be found in the documentation in the installation directory.

The full-text index of enaio® 8.50/8.10 can be deleted and Elasticsearch 2.x uninstalled.

## Update from enaio® 8.0 to enaio® 9.0

Updating enaio® 8.0 to enaio® 9.0 is accomplished by following these steps:

1. Update to enaio® 9.0 via the setup.
2. Installing Elasticsearch 6.x.
3. Installing microservices
  - If the microservice 'index' is installed on the OSFTS computer, the configuration file `index-prod.yml` with the necessary parameters will be created automatically.
  - If not, the configuration file for the microservice 'index' must be extended by the following parameters:  
`osfts.previous.build.version: 5.1.4`
  - Start microservice: The full-text index is created.

Creating the new full-text index will take some time, depending on the size of the full-text data and the existing infrastructure.

4. After the new full-text index has been created: Install and run enaio® index-manager.

Only after the new full-text index has been created and then enriched by enaio® index-manager are the full-text functions completely available.

Details about the enaio® index-manager can be found in the documentation from the installation directory `\Win32\Disk1\Microservices\Index-Manager\`.

# 64-bit Server/Beta

## Installation

With version 9.0, in addition to enaio® server 32-bit version, a 64-bit version is also available as beta. enaio® server in the 64-bit version can be used for test and development environments, but is not yet released for production environments.

Installation and updating of the 32-bit version will continue via the central setup.

enaio® server in the 64-bit version is installed via its own setup from the directory `OSECM_SERVER_X64`. The installation procedure is the same as for the 32-bit installation.

In multi-server installations, 32-bit versions and 64-bit versions can not be mixed, even in different server groups.

At present, only file system-supported archive connections and an iCas driver are available for archiving with 64-bit servers. The iCas driver requires the microservice 'archive'.

Please note that server scripts are now executed in a 64-bit VBScript engine. The use of 32-bit COM DLLs is only possible to a limited extent here. Before an update, the existing scripts should be checked.

## Update to a 64-Bit Server

To upgrade a 32-bit server to a 64-bit server, the following steps are necessary.

### Installation

The 64-bit server is installed on the computer of the 32-bit server.

1. Upgrade to enaio® 9.0 with all components, including 32-bit server.
2. Set up an additional 64-bit system DSN with the same name on the server machine using the 64-bit version of `ODBCad32.exe` from the directory `C:\WINDOWS\system32`.
3. Create an empty database for the 64-bit system DSN. There, empty system tables are created. This database will later be replaced by the existing enaio® database.
4. Stop or disable 32-bit server.
5. Installation of the 64-bit server via the setup from the directory `OSECM_SERVER_X64` on the server computer:
  - You enter the service name, the port, the service account and, if applicable, the server group with the same data entered for the 32-bit server.
  - As the license file, you specify the existing license file of the 32-bit installation.
  - The service requires an administrative account.

You have now completed the installation.

To test, you can change the service control (see below), start the service, and connect via enaio® editor or enaio® administrator with the default user account 'root/optimal'. The 64-bit server is connected to an empty database, there are no users and no object types.

Finish the service again.

## Transfer the Existing Server Settings

The server settings of the 32-bit server are transferred via registry entries to the 64-bit server.

1. Export the 32-bit server settings from the registry of the server computer to a registry file:

```
HKEY_LOCAL_MACHINE\SOFTWARE\Wow6432Node\OPTIMAL  
SYSTEMS\enaio\Schemata
```

2. Modify the path in the registry file with an editor:

Delete \Wow6432Node from the path and save the registry file.

3. Import the registry file.

The registry of the server computer then contains the following keys with the same data:

- 32-bit server:

```
HKEY_LOCAL_MACHINE\SOFTWARE\Wow6432Node\OPTIMAL  
SYSTEMS\enaio\Schemata
```

- 64-bit server:

```
HKEY_LOCAL_MACHINE\SOFTWARE\OPTIMAL  
SYSTEMS\enaio\Schemata
```

4. Connect the 64-bit system DSN to the existing enaio® database.

## Service Control

The server service is still connected in the service control with the 32-bit server and must be converted to the 64-bit server.

Open the command line and execute the following call:

```
sc config SERVICENAME binPath= "{INSTALLDIR64}\axsvckrn.exe -n  
SERVICENAME"
```

Check the startup type for the service and start the service.

Conversely, in the case of update problems, the 64-bit server can be switched back to the 32-bit server at any time:

```
sc config SERVICENAME binPath= "{INSTALLDIR32}\axsvckrn.exe -n  
SERVICENAME"
```

For a deinstallation of the 32-bit server, check its directories: As standard, there are the work and cache area, the etc directory and optionally further optional data. Such data may not be deleted and may need to be removed before uninstalling.

## Archiving with 64-Bit Servers

At present, only file-system-supported archive connections and an iCas/iTernity driver are available for testing archiving with 64-bit servers. Virtual archives require the microservice 'archive'.

The microservice 'archive' is installed via the service manager setup. The configuration file `archive-prod.yml` is located in the directory `\Services\service-manager\config\` after installation.

Profiles must be created in the configuration file for connections to virtual archives.

For iCas/iTernity, a profile scheme is created with the connection data, the user, and the password for the connection that needs to be customized.

For details on the microservice 'archive', see [online](#).

In enaio® enterprise-manager, a virtual archive with the connection data to the microservice 'archive' and the profile name from the configuration file is then created.

Then the archive can be integrated into the media management.

# E-mail Management

## 'E-Mail' Document Type

For the adoption of e-mails, all e-mail document types as of enaio® Version 9.0 require an additional field for the location determination. A field with the internal name 'MAIL\_DIGEST' is automatically created in enaio® editor when creating an e-mail document type. It is positioned so that it is not visible on the data sheet.

For all existing e-mail types, a field for location determination (text field, at least 50 characters) must be added manually.

The standard e-mail document type of enaio® editor contains another change: the date field is no longer created with the data type 'Date' but with the data type 'Date/Time'. For existing e-mail document types, this migration can also be done by data migration in the project.

Changing the data type only via enaio® editor is not possible and would lead to data loss for existing e-mails.

## Service 'mailstorage'

The 'mailstorage' service for e-mail management is required by both enaio® client and the enaio® Outlook NG add-in from the enaio® GroupWise NG add-on.

E-mails and Outlook objects are created as of enaio® Version 9.0 by default in the format 'EML'.

The object definition of each e-mail object type requires a text field (default: MAIL\_DIGEST) for location determination. Object types and index data fields are configured in the following file: \services\service-manager\config\ems-prod.yml.

Example:

```
mapping:
  emsTypes:
    - name: "Email_1"
      internalName: "EMAILTYPE"
      deduplicationContext:
        internalName: "MAIL_DIGEST"
        mode: NONE
      mappingFields:
        - internalName: "MAIL_FROM"
          extractionName: "OS:MailFrom"
        - internalName: "MAIL_TO"
          extractionName: "OS:MailTo"
        - internalName: "MAIL_CC"
          extractionName: "OS:MailCc"
        - internalName: "MAIL_SUBJECT"
          extractionName: "OS:Subject"
        - internalName: "MAIL_BODY"
          extractionName: "OS:MailBody"
        - internalName: "MAIL_SUBMIT_TIME"
          extractionName: "OS:MailDate"
    - name: "Email_2"
      ...
```

If e-mail object types have the internal names of the standard and no other parameters, no configuration is necessary for them.

Configurations can contain further parameters:

- **fixedValue: "value"**  
Fixed value: The value is always entered in the field.
- **defaultValue: "value"**  
The value is only entered in the field if the service 'extraction' does not transmit a value.
- **showIndexdata: true**  
The index data sheet is opened upon creation (default: false).  
When creating multiple e-mails, index data sheets are never opened.

For details on configuring the microservice 'mailstorage', see [online](#).

### MAIL\_DIGEST – Location determination

The field with the internal name 'MAIL\_DIGEST' or an appropriately mapped field is required as of enaio® Version 9.0 for all e-mail object types. In this field, a value for the location determination is entered when creating an e-mail.

E-mails already in enaio® are automatically enriched during operation by the microservice 'mailstorage' with this location information.

Default setting: Every day between 11:00 p.m. and 3:00 a.m. (cron) the data is entered in runs of 1,000 objects. In the event of an error, an error value is entered in the field provided for this purpose.

More information about the cron format can be found here:

<https://www.quartz-scheduler.org/documentation/quartz-2.x/tutorials/crontrigger.html>

The default settings can be adjusted via the configuration file `ems-prod.yml`:

```
autoUpdate:
  activated: true
  maxItems: 1000
  cron: "0+*/1+23,0,1,2+?+*+*+*"
  updateTargetValue: ""
  includeAutoMapped: true
  errorHash: "NO_MAIL_DIGEST"
```

## E-Mail Inbox

The e-mail inbox in enaio® client has already been discontinued and is no longer available with this version.

## E-Mail Viewer

The e-mail viewer is no longer part of enaio® client. E-mails are opened from enaio® client with an external e-mail application. In order for e-mails from enaio® client to be opened correctly in the external e-mail program, this must be selected as the default application in Windows for the file types 'eml' and 'msg'.

## Administrative E-Mails

Administrative e-mails from enaio® server can also be sent SSL-encrypted. To do this, enaio® enterprise-manager specifies the encryption and the corresponding port.

For easier allocation in multi-server systems, the sending server is specified in the subject of the e-mail.

## enaio® exchange

enaio® exchange is converted to the modern Exchange Web Services interface (EWS).

In a new installation, a connection via MAPI is no longer offered in the configuration interface but only the EWS interface. This eliminates some options, such as scripts.

The MAPI interface and the associated features can still be reactivated via a registry key.

**Key:** /OPTIMAL SYSTEMS/OsExchange; **String:** EnableDeprecatedMAPI

For updates to existing installations, the MAPI connection option and related features remain active and can continue to be used after an update without configuration changes.



# Administration

## New System Roles

The following new system roles are available:

- System role 'Subscriptions for others'  
The update will give this role to all users with the 'Manage Subscriptions' role.
- System role 'Resubmissions for others'  
The update gives all users this role.
- System role 'Client: Show workflow substitutes'  
The update gives all users this role.
- System role 'Client: Administer public desktop.'  
Previously, the system role 'Administrator: Configure complete system' was necessary. The update will give users with this role the new role.

## Clauses with Folder Reference

Clauses on register types and document types may refer to the folder data. The index data fields and basic parameters of the assigned folder type are available in addition to the object types fields.

Syntax:

```
folder (folder field Boolean_Operator value)
```

Clauses for a folder type can be combined:

```
folder (folder field1 operator value1 operator folder field2  
operator value2)
```

Combinations of clause with folder reference and clause without folder reference:

```
folder (folder field operator value) operator object field operator  
value)
```

Example – the folder field and the object field cannot be empty:

```
folder ([folder field] is not null) and [object field] is not null
```

Use **Ctrl + Space** to get input support from a suggestion list in the enaio® administrator clause editor.

## Rights Group Control

The new field type 'Rights group control' has the properties of the rights group add-on and the same configuration options via EXTRA entries.

There are differences in the supported field properties and the supported clauses.

In systems with a large number of users and groups, the search and rights calculation is significantly accelerated.

In contrast to the rights group add-on, enaio® client checks the entries against the user administration. User and group names that are currently not available in the user management cannot be saved.

Only enaio® client validates; any data can still be taken over via scripts, interfaces, and import.

Rights group control fields and fields with rights group add-ons can be used in parallel.

To migrate fields with permissions group add-ons to permissions group control fields, the new automatic action 'Rights group conversion' – `axacrgcnv.dll` – is provided after the upgrade.

The conversion takes place in two steps:

- The first step generates the data for those fields with rights group add-ons that are to be switched to the rights group control. This step can be done while the system is running and takes some time, depending on the number of fields, users, and groups.
- The second step may only be performed if the system is not used. It is determined whether additional data has been added to the system after the first step. Missing data is generated and the desired fields with rights group add-ons are converted to rights group control fields in the object definition and the object definition is activated.

Access rights, clauses on access rights, scripts, and export and import actions do not need to be adjusted.

When importing object definitions, the conversion is offered.

Rights group control fields require syntax clauses as of 8.50. Rights group control fields only allow #RIGHTGROUP# clauses and 'is null' clauses. Conversion of fields with rights group add-ons that contain other clauses or that are controlled via scripts is not possible and will result in errors. Also, some field properties are not supported.

## Clauses for Access Rights

For a clearer development of clauses on access rights, conditions can be extended by adding TRUE/FALSE and thus be valid or invalid.

Example: (field1 is not null) or TRUE

This condition is always 'TRUE' in the evaluation.

## Workflow: Permitted Object Types

Use the **Permitted object types** tab of a model in enaio® workflow-editor to specify the types of objects that can be used (with the transfer of objects into a workflow file) to start processes or which may later be placed in a workflow file.

Scripts and import are not affected by these constraints.

Existing process models can be started after the update over all object types and include all object types in the record. Imported models from previous versions also.

enaio® webclient does not yet support this feature.

## Info Area of the Record

The record shows as standard a workspace and an info area. The areas do not have different features. The distinction between workspace and info area can be disabled.

enaio® webclient does not yet support this feature.

## Configuration of the Participant Name

For both the taskflow and, in different contexts, the user selection for forwarding and substitution purposes, the participant name can be configured through the `as.cfg` file:

```
[OXWFDTL]
```

```
LISTCONFIG=%$$Name$$%|%Vorname% %Nachname%
```

Parameter:

%Login% - Login name

%UserId% - User GUID

%Nachname% - Surname

%Vorname% - First name

%E-Mail% - E-Mail address

%\$\$Name\$\$% - Object name

The pipe character serves as a column separator.

Own attributes can also be specified, bracketed by the percent sign. The case is important.

enaio® webclient does not yet support this feature.

## Content Preview

The PDF-based content preview, previously in beta status, is standard for this version.

## Add-Ons

Previously, running an add-on in enaio® client was interpreted as changing the index data, even if that was not the case. To change this behavior, enaio® editor adds the following entry to the add-on configuration:

```
[DATA]
```

```
RESULTOKVALUE=IGNORE
```

## Tables

Tables can be given the property **Supervisor field** in enaio® editor and can therefore only be edited by users with this right.

## W-Templates

Previously, the template restriction was active as standard for W-Documents: Rebuilding a W-Document required a published file format.

This behavior has been changed, the template restriction in enaio® administrator is not active as standard for new installations.

## W-Template Selection via Event Script

The template dialog can be controlled for enaio® client via the event 'BeforeOpen'.

The following options are offered by the script control:

- Filter templates  
Only templates whose names contain a string are offered:
  - It can be specified whether the name begins with the string or ends with the string, or if the string is contained in the name.
  - In addition, it can be specified that the character string is not displayed as part of the name.
- Specify template  
The template is specified; the template dialog is not opened.
- Control options  
Only the option 'create new' is active in the template dialog; the options 'Copy from file' and 'Move from file' are disabled.
- Disable selection

The template dialog is not opened, a document without pages is created.

Filter and template default apply to the templates associated with the user.

#### Script syntax for filters:

```
WriteProfString "GLOBALS", "TEMPLATEFILTER", "<filter>", osfile
asfile.ResultCode = 1
asfile.WriteToFile
```

#### Filter syntax:

Filter	Description
String	The template named <code>string</code> is fixed. The template dialog will not be opened.
Control character \$	Filter
\$String	Filter for templates that begin with the string.
string\$	Filter for templates that end with the string.
\$string\$	Filter for templates that contain the string.
Control character \$	'\$' instead of '#': Filter by hiding the string in the name.
Control character !+	Options: All options available (default). Example: #excel!+
Control character !-	Options: Only the 'Rebuild' option is available. Example: #excel!-

#### Script syntax for disabling the template dialog:

```
WriteProfString "GLOBALS", "SKIPCONTENT", "TRUE", osfile
asfile.ResultCode = 1
asfile.WriteToFile
```

Creates a document without pages.

## System Check

The automatic action 'System Check' has been enhanced with new features:

- Correct mimetype
 

For documents, the MIME type, if not already available, will be added if the MIME type can be assigned based on the file extension.

Missing assignments can be created in the project.
- Correct the number of pages
 

This feature checks if the number of pages of archived documents is stored correctly and corrects corrupt entries.
- Orphaned folder entries

For documents, it determines if location data refers to non-existent folders. Such entries are deleted.

This could leave documents without a location. Therefore, a system check for unbound documents should be done. As a result, such documents are placed in the filing tray of the executing user.

## Authentication with Kerberos

Authentication with Kerberos is now also possible.

Detailed information about this can be found in the administration manual.

## enaio® client – Cache Directory

The cache directory on the client workstations can be specified by an entry in the `asinit.cfg` file.

Example:

```
[CLIENT]
OSTEMP=%LOCALAPPDATA%\enaio\tmp
```

The default directory is: `%LOCALAPPDATA%\Temp\OSTEMP`

## Print out Data of the Security System

When printing security system data, users who have been administratively suspended or whose account validity has expired can be hidden.

## XML Transformation

The automatic action 'XML transformation' logs errors if there are no XML files for transformation in the input directory. In action sequences such error messages can interfere. The 'ignore empty directories' option prevents this.

## COM – GetObjectPattern

GetObjectPattern identifies the title of the specified object as it is used or configured as a window title.

```
GetObjectPattern
(long          lIdent,
long          lType,
long          lMode,
string        Titel)
```

## Server-API - GetResultList/GetObjectDetails

For GetResultList and GetObjectDetails there is the new optional parameter 'RegisterTree':

[RegisterTree] (INT)	1 = Determine register tree information with ID and type in XML form
	0 = Default: no register tree information

## enaio® client

### Color Scheme

In addition to the schemes **white** (standard) and **light gray**, **dark gray** and **black** have been added and a background for the ribbon can also be selected.

### File Format Icon

As an additional static column of the hit list, a file format icon can be selected. As a tooltip, the icon shows the exact file extension.

Since this information is not completely available after an update, the necessary data in the database must be completed via the action 'System cleanup > Correct mimetype'.

Old versions (<6.20) did not detect these mimetypes. Therefore, it can happen in old systems that this action takes a longer time. The work in enaio® is not affected.

If required, additional icons can be added in the project via database changes, and further assignments of file extension and mimetype can be integrated.

If an icon catalog is configured for the first column of a hit list and the icon corresponds to the file format icon, the object type icon is displayed instead of the icon catalog.

All columns of a hit list have received tooltips.

No file format is shown for cross-type reference documents. Likewise, for image documents with several documents of different format.

## Icons for Add-Ons and Buttons

Add-ons received type-specific icons that symbolize the feature.

Example: WWW add-on 

Buttons can also be assigned an icon.

## Substitutions

Substitutions can also be created in enaio® client via the menu **Enaio > Absence**. It now shows who will act as a substitute for the user. This display can be disabled via the new system role 'Client: Show workflow substitutes'.

## Document Sharing

The number of users already marked for shares will be displayed in the dialog. This makes selection in large lists and in the use of filters clearer.

## Hit List Sorting

You can select more columns for multiple sorting with **CTRL+Shift+Click**. The columns are marked.

Sortings can be saved user-specifically and are part of profile administration.

## Pin Column

Using the context menu of a column title, the columns on the left to the current index data column can be fixed in a hit list. When scrolling horizontally, only the columns on the right are scrolled. Pinning is saved with the column configuration.

Fixations can be saved user-specifically and are part of the profile administration.

## Location Focus

The focus when opening a location can be preset on the register tree or list via **Settings > Auto** and then control the keyboard layout after opening a location.

## Register Hit Lists

Up to now, the folder index data from the hit list setting of the document basic parameters were displayed for register hit lists.

Folder index data is now also part of the register basic parameters and could be configured separately.



After an update, register hitlists are displayed without the previously displayed fields of folder index data.

## The Workflow Inboxes

Even for workflows that a user cannot start but in which they are participants, the user can use the settings to configure an inbox.

## Filing tray

W-Documents can also be placed in the filing tray and in the workflow file by the user and by the import also without type.

## Expression

As with the printing of black and white documents, landscape formats can be automatically rotated when printing color and grayscale images.

## Paper Format for Scanning

The scan settings will more closely monitor which paper formats the scanner supports and, if possible, offer additional formats and custom preferences.

# enaio® webclient

## enaio® webclient

For enaio® webclient, service packs will continue to be created at regular intervals in order to fulfill any remaining functionalities.

For this purpose, Technical Release Notes are also published.

## Masks in enaio® webclient

From enaio® Version 9.0, visual equality of masks can be guaranteed in enaio® webclient and enaio® client, if masks are designed according to the instructions in the style guide.

The style guide is available in the installation directory and [online](#).

Via the administration console of enaio® webclient you can switch back to the design of 8.50:

```
com.os.osdrt.ui.responsive.mask.layout = no
```

## enaio® webclient as a Desktop Application

enaio® webclient offers via the user menu the download of enaio® webclient as a desktop application. Via the download enaio® webclient can be installed as a desktop application by the user without administrative rights.

The possibility to download can be administratively disabled.

enaio® webclient as a desktop application can also be installed via an MSI package.

Users require the URL of enaio® gateway, a user name, and a password to log in.

This version corresponds in functionality and user guidance to enaio® webclient, but unlike this has access to the local operating system as a desktop application. As a result, this version can work with applications at workstations, such as the enaio® Office NG add-in.

At workplaces where both enaio® client and enaio® webclient are installed as desktop applications, the enaio® add-ins only connect with enaio® client.

The data transfer with the enaio® Office NG add-in in conjunction with enaio® webclient as desktop application only supports server-side data transfer. Client-side data transfers with dialogs are not executed.

## enaio® mobile

Based on the enaio® webclient, touch-screen-optimized apps (enaio® mobile) are now available for Android and iOS,

enaio® mobile works in concert with enaio® webclient and differs only in its operation, which supports typical touch screen features.

The enaio® mobile installation file is available at the corresponding Google and Apple app stores.



[enaio® mobile for Android](#)

Version 7 or later



[enaio® mobile for iOS](#)

Version 11 or later